

**W3**

9mm L-band Worm-drive Hose clip

DIN: 3017 Light series

Hose Clip **Asfa-L W3** (9mm bandwidth)

Information

Thanks to the exclusive design of the housing, the ASFA LW3 hose clip has excellent performance while being at the same time very compact. The cold-formed stamped band thread, smoothed on the underside, combined with the beveled band edges protects the hose from any damage. The ASFA-L W3 hose clip complies fully with the DIN 3017 norm and also with the RoHs directive EU 2002/95/EC dated 1st July 2006. ASFA LW3 is specially recommended for use in the automotive industry.

Ø Application mm	Reference W3	L max.	s + 0,1 0	h max.	a ± 0,3 0,2	b max.	Max. Values* Torque Nm	Max. Values* Pressure (Bars)	Box Quantity	Packing
8-16	03016014	22,1	0,6	10	9	14	3,0	45	200	800
12-22	03016022	22,1	0,6	10	9	14	3,0	45	200	800
16-27	03016030	23,6	0,7	10	9	14	3,5	42	200	800
20-32	03016049	23,6	0,7	10	9	14	3,5	36	200	800
25-40	03016065	25,6	0,7	10	9	14	4,0	32	100	800
30-45	03016073	25,6	0,7	10	9	14	4,0	28	100	800
32-50	03016081	25,6	0,7	10	9	14	4,0	24	100	800
40-60	03016090	25,6	0,7	10	9	14	4,0	19	100	400
50-70	03016102	29,6	0,7	10	9	14	4,0	17	100	100
60-80	03016110	29,6	0,7	10	9	14	4,0	15	100	100
70-90	03016129	29,6	0,7	10	9	14	4,0	13	50	400
80-100	03016137	29,6	0,7	10	9	14	4,0	11	50	400
90-110	03016145	29,6	0,7	10	9	14	4,0	10	25	200
100-120	03016153	29,6	0,7	10	9	14	4,0	9	25	200
110-130	03016161	29,6	0,7	10	9	14	4,0	8	25	25
120-140	03016170	29,6	0,7	10	9	14	4,0	7	25	25
130-150	03016188	29,6	0,7	10	9	14	4,0	6	25	25
140-160	03016196	29,6	0,7	10	9	14	4,0	5	25	25

* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.

Patented Worldwide.

W3 Materials

Screw:

AISI 430
Stainless steel

Band and housing:

Stainless steel
X6Cr17 (DIN 1.4016)
(AISI-430)

